



# 15.6" BrightSign Built-In 3x1 Video Wall

## Model Numbers

**Standard:** 20-3009-1003

## Display Specifications

**Resolution:** 1920x1080 x3

**Brightness:** 300 nits

**Contrast:** 700 CR

**Viewing Angles:** 89/89/89/89

**Overall Dimensions:** 690 x 378 x 44mm

**Mounting:** VESA 100x100mm M4x10mm

*We build your solution. Ask us about customizing your signage.*

# HS144 Player Specifications

## Audio

- 3.5mm Audio Out (Analog and Digital)

## Storage

- Micro SD Slot
  - SDHC up to 32GB
  - SDXC up to 2TB

## Network

- RJ45 Ethernet

## Input / Output

- 1x USB 2.0
- Phoenix GPIO (4-pin bi-directional terminal block)
- 3.5mm RS-232 Serial Port
- J10: DC 12v 6 pin Power Out
- 3.5mm BrightSign Remote Control Input

## Media Formats

- Video Codecs
  - H.265, H.264 (MPEG-4, Part 10), MPEG-2, MPEG-1
- Video Containers
  - .ts, .mpg, .vob, .mov, .mp4, .m2ts, .wmv
- Images
  - BMP, JPEG, PNG
- Audio
  - MP2, MP3, AAC, WAV
- HTML5 (Moderate Usage)

## BrightSign Features

BrightBeacon™: 2-way Bluetooth/Beacon communication between mobile devices & signage

BrightWall™ : synchronized playback across multiple displays

Zones: playback multiple content types on a single screen

Mosaic Mode: simultaneously play a multitude of smaller resolution videos that add up to the maximum video resolution of the player

Tagging: BrightSign Network users can assign media and player tags for highly targeted content distribution

BrightSign App: update signs with an iOS device

Geo-Fencing: trigger playback based on location (requires USB dongle)

Remote Snapshot: remotely view a snapshot image of the display's playback

BrightPlates™: easy template-based sign creation service

B-deploy: A setup feature to deploy many players at once