



10.1" BrightSign Built-In Finished Screen

Model Numbers

Standard: 20-3008-1083

Touch: 20-3008-1001

PoE: 20-3008-1084

Touch & PoE: 20-3008-1085

Display Specifications

Resolution: 1280x800

Brightness: 400 nits

Contrast: 800 CR

Viewing Angles: 89/89/89/89

Overall Dimensions: 250 x 169 x 40mm

Mounting: VESA 100x100 M4x4mm

We build your solution. Ask us about customizing your signage.

HS124 Player Specifications

Audio

- Stereo 3W HDMI Speakers
 - Finished - Internal
 - Frameless- External, Optional
- 3.5mm Audio Out (Analog and Digital)

Storage

- Micro SD Slot
 - SDHC up to 32GB
 - SDXC up to 2TB

Network

- RJ45 Ethernet

Input / Output

- 1x USB 2.0
- Phoenix GPIO (4-pin bi-directional terminal block)
- 3.5mm RS-232 Serial Port
- J10: DC 12v 6 pin Power Out
- 3.5mm BrightSign Remote Control Input

Media Formats

- Video Codecs
 - H.265, H.264 (MPEG-4, Part 10), MPEG-2, MPEG-1
- Video Containers
 - .ts, .mpg, .vob, .mov, .mp4, .m2ts, .wmv
- Images
 - BMP, JPEG, PNG
- Audio
 - MP2, MP3, AAC, WAV
- HTML5 (Moderate Usage)

BrightSign Features

BrightBeacon™: 2-way Bluetooth/Beacon communication between mobile devices & signage

BrightWall™ : synchronized playback across multiple displays

Zones: playback multiple content types on a single screen

Mosaic Mode: simultaneously play a multitude of smaller resolution videos that add up to the maximum video resolution of the player

Tagging: BrightSign Network users can assign media and player tags for highly targeted content distribution

BrightSign App: update signs with an iOS device

Geo-Fencing: trigger playback based on location (requires USB dongle)

Remote Snapshot: remotely view a snapshot image of the display's playback

BrightPlates™: easy template-based sign creation service

B-deploy: A setup feature to deploy many players at once