

ADDER CCS-PRO4

Управляйте работой четырех компьютеров с одной рабочей станции

О КОМПАНИИ

Adder is a leading developer and thought leader in connectivity solutions. Adder's advanced range of high performance KVM switches, extenders and IP solutions enable the control of local, remote and global IT systems across the enterprise. The company distributes its products in more than 60 countries through a network of distributors, resellers and OEMs. Adder has offices in the United States, United Kingdom, Germany, the Netherlands, Sweden, China and Singapore.

To find out more, visit:
<http://www.adder.com>

ДРУГИЕ ПРОДУКТЫ

Компания Adder всегда готова предложить продукцию для решения ваших задач. Другие устройства которые могут быть полезны и незаменимы:

ADDERView4 PRO DVI
AV4PRO-DVI



ADDERView4 PRO DVI MS
AV4PRO-DVI-DUAL;
AV4PRO-DVI-TRIPLE;
AV4PRO-DVI-QUAD



ADDERLink XD 522
XD-522-DP-PAIR



ADDERLink INFINITY
ALIF1002P, ALIF1002T,
ALIF1002R



ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

Hardware compatibility

All computers equipped with certified USB1.1 and USB2.0 connections.

Software compatibility

All known operating systems for single screens except Linux operating systems, which often have no native support for absolute mouse positioning. Free-Flow works by reporting absolute mouse coordinates. If you wish to use Free-Flow with a Linux operating system then a Udev rule needs to be applied. See the firmware updates page on our website for details. Free-Flow Configuration and firmware upgrade programs are available for use with Windows only.

Computer connections

Audio 3.5mm in x 4, USB type B x 4.

User console connections

Audio 3.5mm out x 1, USB type A x 2 (Console- USB2.0 Low and Full Speed), USB type A x2 (Enumerated USB2.0 Low, Full and Hi-Speed).

USB specification for console connection

Supports up to six Low or Full Speed devices.

Keyboards which support multiple devices behind a hub can now be supported.

The USB class of the supported devices on the console port is limited to HID devices only. It is not possible to use other USB devices e.g. card readers, memory sticks or touch screens on the console port. These devices need to be connected to the enumerated USB ports on the switch.

Physical design

Robust metal construction. 290mm/11.4" (w), 30mm/1.2" (h), 130mm/5.1" (d), 0.90kg/2lbs.

Power

Two 3 pin jack x 2 (one power adapter included), 100-240VAC 50/60Hz, 0.7A, input to power adapter. 12VDC, 18W output from power adapter.

Connection to CCS4:

10p10c connector via cable VSC46.

МОДЕЛИ

CCS-PRO4-XX: CCS-PRO4 Command & Control Switch

XX = код страны
UK = United Kingdom
US = United States
EURO = Europe
AUS = Australia
JP = Japan

АКСЕССУАРЫ

VSC22: Audio Cable 2 meters (3.5mm stereo jack)
VSC24: USB cable 2 meters (type A to B)
RC4-8P8C: RC4 remote 4 button switch and 3 meter cable
CCS-XB: Expansion box for LED illumination of screens (Including 4 light indicators and connection cable VSC46)
CCS-LED: 4 multi-colour LED indicators with 3 meter cable
VSC46: 1 meter connection cable from CCS-XB to CCS-PRO4
PSU-IEC-12VDC-1.5A = optional power supply

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ (Модуля CCS-XB)



Hardware compatibility

For use with CCS4-USB devices with firmware 2.0 or above & CCS-PRO4.

Connections to desk:

10 x 6P6C connectors for the CCS-LED modules. 10P10C connector x 1, for upgrade cable or remote control RC4 4-button switch.

Physical design

Robust metal construction. 95mm/3.7" (w), 30mm/1.2" (h), 65mm/2.6" (d), 0.22kg/1.65lbs.

Operating temperature

0 to 40°C / 32 to 104°F.

Approvals

CE, FCC.



© Copyright 2013 Adder Technology Ltd. All brand names and trademarks are the property of their respective owners. SC-CCS_PRO4_v4.indd