## HDBaseT™ 4x4 MATRIX SELECTOR SWITCHER



- Allows up to 4 HDMI sources to be distributed simultaneously to up to 4 displays
- 4 additional HDMI outputs for flexibility or mirroring capability; allows for connection of up to 8 displays or the ability to create a larger distribution system by cascading or daisy chaining
- HDBaseT Technology that supports HDMI Deep Color- 3D- and up to 1080p High Definition resolution
- Supports Power Over Ethernet (PoE) which integrates power into the Cat5e/Cat6 cable- requiring no power supply for Receiving unit
- Transmission Range: Extends 1080p resolutions up to 230ft (70m)
- Features EDID management which supports default HDMI EDID and has the ability to learn the EDID of display equipment for any "handshake" issues via RS-232 connectivity
- Receivers (sold separately) feature LED indicators for clear power and video signal selection
- HDCP Compliant
- Supports HDMI Deep Color and 3D
- Supports 7.1 channel digital audio
- Wideband IR pass-through (20kHz to 60 kHz)
- Choose from 5 switching modes front panel buttons- Local remote control- RS-232 control- IR call-back (dedicated IR extension cable connected to IR extension port- and IR emitters on sources required)- and IP control utilizing smartphone or tablet via LAN
- 24V 3.75A DC- UL Listed Power supply for 4×4 matrix



Part Number: EVMX4004